

UNSKIRTED STORAGE SILOS							
DIAMETER	MODEL NUMBER	APPROXIMATE CAPACITY				HEIGHT TO LID	
		MAXIMUM		USABLE W/30° ANGLE OF REPOSE			
		Cu. Ft.	M <sup>3</sup>	Cu. Ft.	M <sup>3</sup>	FEET	METERS
6 Ft. (1.8m) Diameter 60° Hopper	C45-00601	124	4	113	3	10.2	3.1
	C45-00602	199	6	188	5	12.8	3.9
	C45-00603	273	8	262	7	15.5	4.7
	C45-00604	348	10	337	10	18.2	5.5
	C45-00605	423	12	412	12	20.8	6.3
	C45-00606	497	14	486	14	23.5	7.2
9 Ft. (2.7m) Diameter 45° Hopper	C45-00932	439	12	385	11	13.0	4.0
	C45-00933	608	17	554	16	15.8	4.8
	C45-00934	777	22	723	20	18.5	5.6
	C45-00935	946	27	892	25	21.2	6.5
	C45-00936	1,115	32	1,061	30	23.8	7.3
	C45-00937	1,284	36	1,230	35	26.4	8.0
	C45-00938	1,453	41	1,399	40	29.0	8.8
	C45-00939	1,622	46	1,568	44	31.7	9.7
	C45-009310	1,791	51	1,737	49	34.3	10.5
	C45-009311	1,960	56	1,906	54	37.0	11.3
9 Ft. (2.7m) Diameter 60° Hopper	C45-00902	514	15	460	13	16.0	4.9
	C45-00903	684	19	630	18	18.6	5.7
	C45-00904	854	24	800	23	21.3	6.5
	C45-00905	1,019	29	965	27	24.0	7.3
	C45-00906	1,189	34	1,135	32	26.6	8.1
	C45-00907	1,359	38	1,305	37	29.3	8.9
	C45-00908	1,529	43	1,475	42	31.9	9.7
	C45-00909	1,699	48	1,645	47	34.6	10.5
	C45-009010	1,869	53	1,815	51	37.3	11.4
	12 Ft. (3.7m) Diameter 45° Hopper	C45-01232	803	23	662	19	14.9
C45-01233		1,102	31	961	27	17.6	5.4
C45-01234		1,400	40	1,259	36	20.3	6.2
C45-01235		1,698	48	1,557	44	22.9	7.0
C45-01236		1,997	57	1,856	53	25.6	7.8
C45-01237		2,295	65	2,154	61	28.3	8.6
C45-01238		2,593	73	2,452	69	31.0	9.4
C45-01239		2,892	82	2,751	78	33.6	10.2
C45-012310		3,190	90	3,049	86	36.3	11.1
C45-012311		3,489	99	3,348	95	39.0	11.9

UNSKIRTED STORAGE SILOS							
DIAMETER	MODEL NUMBER	APPROXIMATE CAPACITY				HEIGHT TO LID	
		MAXIMUM		USABLE W/30° ANGLE OF REPOSE			
		Cu. Ft.	M <sup>3</sup>	Cu. Ft.	M <sup>3</sup>	FEET	METERS
12 Ft. (3.7m) Diameter 60° Hopper	C45-01202	966	27	825	23	18.8	5.7
	C45-01203	1,265	36	1,124	32	21.5	6.6
	C45-01204	1,563	44	1,422	40	24.1	7.3
	C45-01205	1,861	53	1,720	49	26.8	8.2
	C45-01206	2,160	61	2,019	57	29.5	9.0
	C45-01207	2,459	70	2,318	66	32.2	9.8
	C45-01208	2,758	78	2,617	74	34.8	10.6
	C45-01209	3,057	87	2,916	83	37.5	11.4
	C45-012010	3,356	95	3,215	91	40.2	12.3
	C45-012011	3,655	103	3,514	100	42.9	13.1
15 Ft. (4.6m) Diameter 45° Hopper	C45-01532	1,386	39	1,096	31	16.7	5.1
	C45-01533	1,854	52	1,564	44	19.3	5.9
	C45-01534	2,323	66	2,033	58	22.0	6.7
	C45-01535	2,792	79	2,502	71	24.7	7.5
	C45-01536	3,261	92	2,971	84	27.3	8.3
	C45-01537	3,730	106	3,440	97	30.0	9.1
	C45-01538	4,199	119	3,909	111	32.7	10.0
15 Ft. (4.6m) Diameter 60° Hopper	C45-01539	4,668	132	4,378	124	35.4	10.8
	C45-01502	1,734	49	1,444	41	21.6	6.6
	C45-01503	2,200	62	1,910	54	24.3	7.4
	C45-01504	2,666	75	2,376	67	26.9	8.2
	C45-01505	3,132	89	2,842	80	29.6	9.0
	C45-01506	3,599	102	3,309	94	32.3	9.8
	C45-01507	4,065	115	3,775	107	34.9	10.6
	C45-01508	4,531	128	4,241	120	37.6	11.5
18 Ft. (5.5m) Diameter 45° Hopper	C45-01832	2,120	60	1,600	45	19.0	5.8
	C45-01833	2,791	79	2,271	64	21.7	6.6
	C45-01834	3,463	98	2,943	83	24.3	7.4
	C45-01835	4,134	117	3,614	102	27.0	8.2
	C45-01836	4,805	136	4,285	121	29.7	9.1
	C45-01837	5,476	155	4,956	140	32.4	9.9
	C45-01838	6,148	174	5,628	159	35.0	10.7
	C45-01839	6,820	193	6,300	178	37.3	11.4



**BROCK INDUSTRIAL SYSTEMS**

Phone: +1 866-658-4191

www.brockindustrial.com

Email: sales@brockgrain.com